

SAFETY DATA SHEET

GHS

United States

Section 1. Product and company identification

Product name VANLUBE® SB In case of emergency

1-203-853-1400

50928 Code

Chemtrec: 1-800-424-9300 Supplier/Manufacturer Vanderbilt Chemicals, LLC

Outside US: 30 Winfield Street +1-703-527-3887 Norwalk, CT 06855

Synonym Sulfurized isobutylene.

Lubricant additives **Material uses**

Liquid. **Product type**

Section 2. Hazards identification

OSHA/HCS status This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the

substance or mixture

FLAMMABLE LIQUIDS - Category 4

GHS label elements

Warning Signal word

Hazard statements Combustible liquid.

Precautionary statements

Prevention Wear protective gloves. Wear eye or face protection: Recommended: safety glasses

with side-shields. Keep away from flames and hot surfaces. - No smoking.

Response Not applicable.

Store in a well-ventilated place. Keep cool. **Storage**

Disposal Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Hazards not otherwise

Headspace of storage vessel may contain small amounts (ppm levels) of hydrogen sulfide. classified

Section 3. Composition/information on ingredients

Mixture Substance/mixture

Ingredient name	CAS number	% by weight
sulfurized isobutylene	68511-50-2	>99

Occupational exposure limits, if available, are listed in Section 8.

Validation date 5/6/2014. Date of previous issue : No previous validation. 1/11

Section 4. First aid measures

Description of necessary first aid measures

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention if irritation occurs.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If

not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical

attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean

shoes thoroughly before reuse.

Ingestion Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and

keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contactNo known significant effects or critical hazards.InhalationNo known significant effects or critical hazards.Skin contactNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contactNo specific data.InhalationNo specific data.Skin contactNo specific data.IngestionNo specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments No specific treatment.

Protection of first-aidersNo action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Validation date : 5/6/2014. Date of previous issue : No previous validation. 2/11

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

Use dry chemical, CO₂, water spray (fog) or foam.

Do not use water jet.

Specific hazards arising from the chemical

Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide metal oxide/oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters Remark

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Hydrogen disulfide may be released at temperatures above 60°C (140°F)

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the

Validation date : 5/6/2014. Date of previous issue : No previous validation. 3/11

Section 6. Accidental release measures

same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Headspace of storage vessel may contain small amounts (ppm levels) of hydrogen sulfide.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
hydrogen sulfide	ACGIH TLV (United States, 6/2013).
	TWA: 1 ppm 8 hours.
	STEL: 5 ppm 15 minutes.
	OSHA PEL 1989 (United States, 3/1989).
	TWA: 10 ppm 8 hours.
	TWA: 14 mg/m³ 8 hours.
	STEL: 15 ppm 15 minutes.
	STEL: 21 mg/m³ 15 minutes.
	OSHA PEL Z2 (United States, 2/2013).
	CEIL: 20 ppm
	AMP: 50 ppm 10 minutes.
	NIOSH REL (United States, 10/2013).
	CEIL: 10 ppm 10 minutes.
	CEIL: 15 mg/m³ 10 minutes.

Validation date : 5/6/2014. Date of previous issue : No previous validation. 4/11

Section 8. Exposure controls/personal protection

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: splash goggles

Skin protection

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: lab coat

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Personal protective equipment (Pictograms)



Section 9. Physical and chemical properties

Appearance

Physical state Liquid.

Color Clear Amber.
Odor Pungent. [Slight]
Odor threshold Not available.
pH Not available.

Validation date : 5/6/2014. Date of previous issue : No previous validation. 5/11

Section 9. Physical and chemical properties

Melting pointNot available.Boiling pointNot available.

Flash point Closed cup: >80°C (>176°F) [Pensky-Martens.]

Open cup: 110°C (230°F) [Cleveland.]

Burning time

Burning rate

Evaporation rate

Flammability (solid, gas)

Lower and upper explosive

Not applicable.

Not available.

Not available.

Not available.

(flammable) limits

Vapor pressure 0.069 kPa (0.52 mm Hg) [50°C]

Vapor density >1 [Air = 1] Relative density 1.135

Solubility Insoluble in the following materials: cold water.

Solubility in water
Partition coefficient: n-

octanol/water

Not available. Not available.

Auto-ignition temperature

Decomposition temperature

Not available.

Not available.

Not available.

Viscosity Kinematic (40°C (104°F)): 0.59 cm²/s (59 cSt)

Section 10. Stability and reactivity

ReactivityNo specific test data related to reactivity available for this product or its ingredients.

Chemical stability The product is stable.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld,

braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not

allow vapor to accumulate in low or confined areas.

Avoid temperatures above 60°C (140°F) as hydrogen disulfide may be released.

Incompatible materials Reactive or incompatible with the following materials:

oxidizing materials

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Validation date : 5/6/2014. Date of previous issue : No previous validation. 6/11

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
sulfurized isobutylene	LD50 Dermal		38700 mg/kg	-
	LD50 Oral	Rat	6500 mg/kg	-

Irritation/Corrosion

Conclusion/Summary

Skin Non-irritating to the skin.

Eyes Non-irritating to the eyes.

Respiratory Non-irritating to the respiratory system.

Sensitization

Skin Not available.

Mutagenicity

Conclusion/Summary Non-mutagenic for mammalians.

Carcinogenicity

Conclusion/Summary Not available.

Reproductive toxicity

Conclusion/Summary Not available.

Teratogenicity

Conclusion/Summary Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Information on the likely routes of exposureRoutes of entry anticipated: Oral, Inhalation.
Routes of entry not anticipated: Dermal.

Potential acute health effects

Eye contactNo known significant effects or critical hazards.InhalationNo known significant effects or critical hazards.Skin contactNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact No specific data.

Validation date : 5/6/2014. Date of previous issue : No previous validation. 7/11

Section 11. Toxicological information

InhalationNo specific data.Skin contactNo specific data.IngestionNo specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

Not available.

effects

Potential delayed effects No.

Not available.

Long term exposure

Potential immediate

Not available.

effects

Potential delayed effects Not ava

Not available.

Potential chronic health effects

Conclusion/Summary Not available.

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Ecotoxicity

Conclusion/Summary Not available.

Persistence and degradability

Not available.

Other adverse effects No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methodsThe generation of waste should be avoided or minimized wherever possible. Disposal

of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered

Validation date : 5/6/2014. Date of previous issue : No previous validation. 8/11

Section 13. Disposal considerations

when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not regulated.	_	-	-		Remarks For bulk (> 119 gallons) packages, this material is regulated under U. S. Department of Transportation regulations for domestic shipments. Its proper shipping description is NA 1993, combustible liquid, n.o.s., PG III.
TDG Classification	Not regulated.	-	-	-		-
ADR/RID Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA-DGR Class	Not regulated.	-	-	-		-

PG*: Packing group

Section 15. Regulatory information

United States inventory (TSCA 8b) All components are listed or exempted.

U.S. Federal regulations

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

Clean Water Act (CWA) 311: hydrogen sulfide

SARA 302/304

Composition/information on ingredients

Validation date : 5/6/2014. Date of previous issue : No previous validation. 9/11

Section 15. Regulatory information

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
hydrogen sulfide	<0.1	Yes.	-	-	100	-

SARA 311/312

Classification Fire hazard Composition/information on ingredients

No products were found.

State regulations

MassachusettsNone of the components are listed.New YorkNone of the components are listed.New JerseyNone of the components are listed.PennsylvaniaNone of the components are listed.California Prop. 65None of the components are listed.

International regulations

Europe inventory All components are listed or exempted.

Canada inventory
Australia inventory (AICS)
All components are listed or exempted.
China inventory (IECSC)
All components are listed or exempted.
All components are listed or exempted.
All components are listed or exempted.
Korea inventory
All components are listed or exempted.
All components are listed or exempted.
New Zealand Inventory of
All components are listed or exempted.

Chemicals (NZIoC)

Philippines inventory (PICCS) All components are listed or exempted.

Section 16. Other information



The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



History

Date of printing 5/6/2014. **Validation date** 5/6/2014.

Date of previous issue No previous validation.

Version 1

Validation date : 5/6/2014. Date of previous issue : No previous validation. 10/11

Section 16. Other information

Key to abbreviations ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References Not available.

Information contact Vanderbilt Global Services, LLC

Corporate Risk Management

1-203-295-2143

Visit www.vanderbiltchemicals.com for more information.

Notice to reader

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liability with respect to the use of any material supplied by us.

Validation date : 5/6/2014. Date of previous issue : No previous validation. 11/11